

All dimensions in mm
Finish is gold plate

Contact



Unit 5, Chancerygate B/Centre,
Surrey KT6 7RA, England
www.latechniques.com

Manufactured in the UK
Specification subject to change without notification



LA Techniques Ltd

LA32-04-10 DUAL 20 Gb/s DRIVER AMPLIFIER



The LA32-04-10 is a power amplifier mainly intended for use as an optical modulator driver. It is able to support data rates to 2 x 23 Gb/s with good pulse response and low jitter. Some of its key features are as follows.





- 30 kHz - 20 GHz Bandwidth
- > 7 v_{pp} Output at 23 Gb/s
- Low power dissipation (<3 W per channel)
- Crossover adjustment
- Output level control
- Output level detector
- Environmentally sealed
- Cost effective

Electrical Specification
(0°C to +60°C Case Temperature)

Parameter	Units	Min	Typ	Max
Bandwidth				
Low frequency 3 dB point	kHz	-	30	60
High frequency 3 dB point	GHz	18	19	-
Gain (non-inverting)	dB	24	25	30
Gain ripple				
500 kHz - 16 GHz	dB	-	±2.0	±3.5
Input return loss (f < 16 GHz)	-	8	10	-
Output return loss (f < 16 GHz)	-	8	10	-
Output voltage ² , V _{max}	V _{pp}	7.0	8.0	-
Output voltage control range	V _{pp}	4.0	-	V _{max}
Output control voltage range	V	-10	-	-1
Output temperature stability ⁴	%	-	5	10
Detector output ¹	V	-	0.45	-
Detector output resistance	kΩ	-	15	17
Pulse characteristics ^{1,2,3}				
Rise time (10 – 90%)	ps	-	15	20
Fall time (10 – 90%)	ps	-	15	20
Over / undershoot	%	-	5	10
Droop (time < 10 ns)	%	-	5	-
Jitter (peak to peak)	ps	-	5	8
Typical crossover adjustment range ¹	%	-5	-	+5
Crossover control voltage range	V	-5	-	+5
Supply voltage (positive)	V	+8.2	+8	+7.8
Supply current (positive) ^{1,2}	mA	-	340	400
Supply voltage (negative)	V	-4.9	-5	-5.1
Supply current (negative) ²	mA	-	55	65
Operating case temperature	°C	-10	-	+65

- Notes: 1. 20 Gb/s 2²³-1 PRBS data, 7.0 V_{eye} output
 2. 0.5 V_{pp} input drive, 18 ps input rise / fall time, per channel
 3. Output set < 7 V_{pp}
 4. Output set between 5 and 7 V_{pp} at 25°C

20 Gb/s Eye Diagram
(output set to 7V)



CH 2 - S21
 0.0000 mm REF
 0.000 dB OFFSET
 0.00° OFFSET

MARKER 1
 19.120000000 GHz
 21.005 dB

MARKER TO MAX
 MARKER TO MIN

Small signal response

MARKER READOUT FUNCTIONS